

Cisco

500-710

Cisco Video Infrastructure Implementation

For More Information – Visit link below:

<https://www.examsempire.com/>

Product Version

- 1. Up to Date products, reliable and verified.**
- 2. Questions and Answers in PDF Format.**



<https://examsempire.com/>

Latest Version: 10.0

Question: 1

Which two administrative functions can a Cisco Spark Partner reseller perform from the Cisco Spark Management portal? (Choose two.)

- A. Quickly start customer trials.
- B. Determine Single Sign-On customer usage reports.
- C. Enable Single Sign-On and Directory sync through corporate LDAP services on-premises.
- D. Determine role-based access and view usage reports.
- E. Help to manage the customer accounts.

Answer: AE

Question: 2

Which two ports are used for SIP communications between an endpoint and the SIP server? (Choose two.)

- A. 1719 (TCP)
- B. 5061 (TLS)
- C. 1721 (TLS)
- D. 5060 (TCP)
- E. 1720 (TCP)

Answer: BD

Question: 3

Which statement about Microsoft Skype for Business interoperability with Cisco Meeting Server is true?

- A. Calls cannot be placed between S4B and Cisco Meeting App users
- B. Local directories can always be used between S4B users and CMA
- C. Chat can be used between S4B and Cisco Meeting App users
- D. Chat can be used between S4B and Cisco Meeting Server Spaces

Answer: B

Question: 4

An engineer wants to only allow the registration of endpoints with aliases containing cisco.com as the domain. Which option accomplishes this task?

- A. Set the restriction policy to "Deny" and include the expression.*@*in the deny list.
- B. Set the restriction policy to "Allow" and include the expression\|@ cisco.com in the allow list.
- C. Set the restriction policy to "Allow" and include the expression. *@cisco. com in the allow list.

D. Set the restriction policy to "None" and include the expression \1@ cisco.com in the allow list.

Answer: C

Question: 5

Which statement about the deployment of Cisco Conductor with Cisco Telepresence Server for Rendezvous Conferences is true?

- A. Conductor must be added to the TMS database.
- B. A SIP trunk must be established between Conductor and the TelePresence Server.
- C. A neighbor zone and search rules must be built between the Expressway and the Conductor.
- D. A neighbor zone and search rules must be built between the Expressway and TelePresence Server.

Answer: C

Thank You for Trying Our Product

Special 16 USD Discount Coupon: **NSZUBG3X**

Email: support@examsempire.com

**Check our Customer Testimonials and ratings
available on every product page.**

Visit our website.

<https://examsempire.com/>