

Oracle 1Z0-888

MySQL 5.7 Database Administrator

For More Information – Visit link below:

<https://www.examsempire.com/>

Product Version

1. Up to Date products, reliable and verified.
2. Questions and Answers in PDF Format.



<https://examsempire.com/>

Visit us at: <https://www.examsempire.com/1z0-888>

Latest Version: 12.0

Question: 1

You have just executed a manual backup by using this command:

```
mysqlbackup -u root -p --socket=/tmp/my.sock --backup-dir=/my/backup/ backup
```

The operation completed without error.

What is the state of this backup and operation required before it is ready to be restored?

- A. Backup State = Compressed BackupOperation = copy-back
- B. Backup State = Raw BackupOperation = apply-log
- C. Backup State = Prepared BackupOperation = validate
- D. Backup State = Prepared BackupOperation = apply-log
- E. Backup State = Raw BackupOperation = backupdir-to-image

Answer: E

Question: 2

Which MySQL utility program should you use to process and sort the Slow Query Log based on query time or average query time?

- A. mysqldumpslow
- B. mysqldump
- C. mysqlaccess
- D. mysqlshow
- E. mysqlslow

Answer: A

Question: 3

Consider:

```
mysql> EXPLAIN SELECT * FROM City WHERE Name = 'Jacksonville' AND
CountryCode = 'USA'\G
***** 1. row *****
id: 1
select_type: SIMPLE
table: City
type: ref
possible_keys: name_country_index
key: name_country_index
key_len: 13
ref: const, const
rows: 1
Extra: Using where
```

Which statement best describes the meaning of the value for the key_len column?

- A. It shows how many bytes will be used from each index row.
- B. It shows the number of characters indexed in the key.
- C. It shows the total size of the index row.
- D. It shows how many columns in the index are examined.

Answer: A

Question: 4

Examine the mydata table and SELECT statements:

```
CREATE TABLE `mydata` (
  `id` int(11) NOT NULL AUTO_INCREMENT,
  `a` int(11) DEFAULT NULL,
  `b` int(11) DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `a_idx` (`a`)
) ENGINE=InnoDB;
```

```
mysql>SELECT @@session.transaction_isolation;
+-----+
|@@ session.transaction_isolation |
+-----+
| REPEATABLE-READ                  |
+-----+
1 row in set (0.00 sec)
```

```
mysql> SELECT * from mydata;
+----+----+-----+
|id  | a  | b  |
+----+----+-----+
|1   | 1  | 1  |
|2   | 1  | 1  |
|3   | 2  | 2  |
|4   | 2  | 2  |
|5   | 2  | 3  |
+----+----+-----+
```

You issue:

```
mysql> begin;
```

```
mysql> update mydata set a=0 where b=3;
```

How many rows are now protected by locks with the default InnoDB configuration?

- A. one
- B. one row and a next-key lock for supremum
- C. one row and a gap-lock
- D. five

Answer: D

Question: 5

A particular government's security policy is to have very strict data encryption and safety settings. This is done by restricting access based on their own CA authority and limiting access to particular users within a department. Which method could be used to restrict access as required?

- A. using GRANT ... REQUIRE X509 AND REQUIRE ISSUER '/C=.....' AND REQUIRE SUBJECT '/C=.....'

- B. using GRANT USAGE, X509,ON *.* TO user@remotehost IDENTIFIED BY 'secret_password'
- C. using GRANT ... REQUIRE SSL for a secure connection
- D. using GRANT USAGE, SSL,ON *.* TO user@remotehost IDENTIFIED BY 'secret_password'

Answer: A

Thank You for Trying Our Product
Special 16 USD Discount Coupon: NSZUBG3X
Email: support@examsempire.com

**Check our Customer Testimonials and ratings
available on every product page.**

Visit our website.

<https://examsempire.com/>