

Nokia 4A0-104

Nokia Services Architecture

For More Information – Visit link below:

<https://www.examsempire.com/>

Product Version

1. Up to Date products, reliable and verified.
2. Questions and Answers in PDF Format.



<https://examsempire.com/>

Visit us at: <https://www.examsempire.com/4a0-104>

Latest Version: 11

Question: 1

VPWS allows carriers to offer services such as point-to-point frame-relay, ATM, and Ethernet on a single platform without the need for multiple overlay networks.

- A. TRUE
- B. FALSE

Answer: A

Question: 2

Which of the following best describes a VPLS?

- A. Layer 3 direct Internet access service.
- B. Layer 2 point-to-point service.
- C. Layer 2 multipoint-to-multipoint service.
- D. Layer 3 IP multipoint-to-multipoint VPN service

Answer: C

Question: 3

Which of the following is NOT a VPWS service supported on the Alcatel-Lucent 7750 SR?

- A. Epipe
- B. Fpipe
- C. Apipe
- D. Lpipe
- E. Cpipe
- F. Gpipe

Answer: F

Question: 4

A service can be either local or distributed.

- A. TRUE
- B. FALSE

Answer: A

Question: 5

When configuring distributed services across a network, it is considered best practice to configure which of the following parameters as globally significant? (Choose 2)

- A. SDP ID
- B. Service ID
- C. Customer ID
- D. SAP ID

Answer: B, C

Question: 6

When a physical port is configured for null encapsulation, many SAPs can be configured using that port.

- A. TRUE
- B. FALSE

Answer: B

Question: 7

Which of the following statements is FALSE regarding SAPs?

- A. VPWS: SAPs can be defined on Ethernet, POS, Sonet/SDH, or TDM channels.
- B. VPWS: Two SAPs are defined for a service that originates and terminates on the same Alcatel-Lucent 7750 SR
- C. VPLS: More than two SAPs can be defined in a service.
- D. VPWS: SAPs are associated with an IP interface.

Answer: D

Question: 8

SAPs in an Epipe service can only be configured on Ethernet ports

- A. TRUE
- B. FALSE

Answer: B

Question: 9

Which of the following commands is used to configure the encapsulation type of an Ethernet port?

- A. configure ethernetencap-typedot1q|null|qinq port port-id
- B. configure service port port-id ethernetencap-typedot1q|null|qinq create
- C. configure port port-id ethernetencap-type dot1q|null|qmq
- D. configure service service-id ethernetencap-type dot1q|null|qinq create

Answer: C

Question: 10

Which of the following best describes a distributed Epipe Service?

- A. AnEpipe that has 2 or more SDPs configured.
- B. AnEpipe that has 3 or more SAPs configured.
- C. AnEpipe that has 2 SAPs on the same node but no SDPs configured
- D. AnEpipe that is configured between two nodes, each having 1 SAP and 1 SDP configured.

Answer: D

Thank You for Trying Our Product

Special 16 USD Discount Coupon: NSZUBG3X

Email: support@examsempire.com

**Check our Customer Testimonials and ratings
available on every product page.**

Visit our website.

<https://examsempire.com/>