

# Huawei

## H35-561

### HCNP - LTE RNP & RNO

For More Information – Visit link below:

<https://www.examsempire.com/>

**Product Version**

1. Up to Date products, reliable and verified.
2. Questions and Answers in PDF Format.



<https://examsempire.com/>

Visit us at: <https://www.examsempire.com/h35-561>

# Latest Version: 6.0

## Question: 1

Which of the following events can be used to trigger inter-frequency switching? (multiple choice)

- A. A2
- B. A3
- C. A4
- D. A5

**Answer: B, C, D**

## Question: 2

How many types of TDD uplink and downlink subframe configurations are there?

- A. 3
- B. 5
- C. 7
- D. 9

**Answer: C**

## Question: 3

When X2 handover cannot be performed between eNodeBs, S1 handover is performed.

- A. True
- B. False

**Answer: A**

## Question: 4

How many configurations are there for R8 TDD special subframe configuration?

- A. 3

- B. 5
- C. 7
- D. 9

**Answer: D**

### Question: 5

In which of the following messages will the tracking area information be sent to the MME for consistency check?

- A. S1AP: E-RAB setup request
- B. RRC: RRC connection request
- C. S1AP: Initil context setup request
- D. S1AP: S1 setup request

**Answer: D**

**Thank You for Trying Our Product**

**Special 16 USD Discount Coupon: NSZUBG3X**

**Email:** [support@examsempire.com](mailto:support@examsempire.com)

**Check our Customer Testimonials and ratings  
available on every product page.**

**Visit our website.**

**<https://examsempire.com/>**